



High Efficient Surface Mount Rectifiers

Reverse Voltage 50 to 1000 Volts Forward Current 1.0 Ampere



Features

- For surface mounted application
- Glass passivated junction chip
- Low forward voltage drop
- Low profile package
- Built-in strain relief, ideal for automatic placement
- Fast switching for high efficiency
- Plastic material used carries underwriters laboratory classification 94V-O
- High temperature soldering : 260°C /10 seconds at terminals

Mechanical Data

- Case : Molded plastic
- Terminals : Solder plated
- Polarity : Indicated by cathode band
- Packaging : 12mm tape per EIA STD RS-481
- Weight : 0.064gram

Marking



Maximum Ratings & Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified

Single phase half wave 60 Hz, resistive or inductive load

For capacitive load, derate current by 20%

Parameter	Symbol	US1A	US1B	US1D	US1G	US1J	US1K	US1M	Unit	Remark				
Maximum Repetitive Peak Reverse Voltage	V _{RRM}	50	100	200	400	600	800	1000	V					
Maximum RMS Voltage	V _{RMS}	35	70	140	280	420	560	700	V					
Maximum DC Blocking Voltage	V _{DC}	50	100	200	400	600	800	1000	V					
Maximum Average Forward Rectified Current See Fig.1	I _{F(AV)}	1.0						A						
Peak Forward Surge Current 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC Method)	I _{FSM}	30						A						
Maximum Instantaneous Forward Voltage @ 1.0A	V _F	1.0		1.3		1.7		V						
Maximum DC Reverse Current at Rated DC Blocking Voltage	I _R	5.0						uA	Ta=25°C					
		150						uA	Ta=125°C					
Maximum Reverse Recovery Time	trr	50		75		ns		Note 1						
Typical Junction Capacitance	C _J	15		10		pF		Note 2						
Typical Thermal Resistance	R _{th(j-a)}	75						°C /W	Note 3					
	R _{th(j-l)}	27												
Operation Junction Temperature Range	T _J	-55 to +150						°C						
Storage Temperature Range	T _{STG}	-55 to +150						°C						

Note 1. Reverse Recovery Time Test Conditions : I_F=0.5A, I_R=1.0A, I_{RR}=0.25A

Note 2. Measured at 1MHz and Applied Reverse Voltage of 4.0Volts D.C.

Note 3. Mounted on P.C.B with 0.2"×0.2" (5mm×5mm) Copper Pad Areas



Ratings and Characteristics Curves ($T_a=25^\circ\text{C}$ unless otherwise noted)




Fig.2 Maximum Non-Repetitive Peak Forward Surge Current




Fig.3 Typical Instantaneous Forward Characteristics




Fig.4 Typical Junction Capacitance




Fig.5 Typical Reverse Characteristics




Fig.6 Reverse Recovery Time Charateristic and Test Circuit Diagram

